

SAFETY DATA SHEET

Issue Date 01-Apr-2013 Revision Date 19-May-2015 Version 1

1. PRODUCT AND COMPANY IDENTIFICATION

Product identifier

Product Code 15770

Product Name HD Pride Cleaner

Other means of identification

Recommended use of the chemical and restrictions on use

Use only for the purpose on the product label.

Details of the supplier of the safety data sheet

Manufacturer / Manufactured For

Seatex, Ltd. 445 TX Hwy 36 Rosenberg, TX 77471 Phone: (800) 829-3020

Emergency telephone number

24 Hour Emergency Phone Number 1-800-535-5053

2. HAZARDS IDENTIFICATION

Classification

Acute toxicity - Oral	Category 5
Skin corrosion/irritation	Category 1 Sub-category B
Serious eye damage/eye irritation	Category 1
Acute aquatic toxicity	Category 3
Chronic aquatic toxicity	Category 3

Label elements

Emergency Overview

Danger

Hazard statements

May be harmful if swallowed Causes severe skin burns and eye damage Harmful to aquatic life with long lasting effects



Appearance Colorless to Very Pale Yellow

Physical state Liquid

Odor Surfactant

Precautionary Statements - Prevention

Use personal protective equipment as required. Do not breathe dust/fume/gas/mist/vapors/spray. Wash face, hands and any exposed skin thoroughly after handling. Keep away from heat/sparks/open flames/hot surfaces. — No smoking. Avoid release to the environment.

Precautionary Statements - Response

Specific Treatment (See Section 4 on the SDS).

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. See a physician.

IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower. Wash contaminated clothing before reuse. If burns develop, see a physician.

IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Immediately call a POISON CENTER or doctor/physician.

IF SWALLOWED: Rinse mouth. DO NOT induce vomiting. Drink plenty of water. See a physician immediately.

Precautionary Statements - Storage

Store locked up. Keep out of reach of children.

Precautionary Statements - Disposal

Dispose of contents/container to an approved waste disposal plant.

Hazards not otherwise classified (HNOC)

Other Information

3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Name	CAS No.	Weight-%	Trade Secret
Potassium Hydroxide	1310-58-3	1-5	*
2-butoxyethanol	111-76-2	1-5	*
Sodium Dodecylbenzene Sulfonate	25155-30-0	1-5	*
Sodium Metasilicate	6834-92-0	1-5	*

^{*}The exact percentage (concentration) of composition has been withheld as a trade secret.

4. FIRST AID MEASURES

First aid measures

Skin Contact Wash off immediately with soap and plenty of water while removing all contaminated

clothes and shoes. Wash contaminated clothing before reuse. If irritation persists or burns occur, get medical attention. For minor skin contact, avoid spreading material on unaffected

skin. For severe burns, immediate medical attention is required.

Eye contact Immediate medical attention is required. Immediately flush with plenty of water. After initial

flushing, remove any contact lenses and continue flushing for at least 15 minutes. Keep eye

wide open while rinsing. Do not rub affected area.

Inhalation If mists/vapors are formed or irritation occurs, leave area and do not return until

mists/vapors have dissipated. If irritation persists, call a physician. If breathing is difficult, give oxygen. If breathing has stopped, give artificial respiration. Get medical attention

immediately.

Immediate medical attention is required. Rinse mouth. Do NOT induce vomiting. Drink

plenty of water. Never give anything by mouth to an unconscious person.

Most important symptoms and effects, both acute and delayed

Symptoms Irritation or burning to mucous membranes. May cause irritation and/or burning to eyes and

skin.

Indication of any immediate medical attention and special treatment needed

Note to physicians Product is a corrosive material. Use of gastric lavage or emesis is contraindicated.

Possible perforation of stomach or esophagus should be investigated. Do not give chemical antidotes. Asphyxia from glottal edema may occur. Marked decrease in blood pressure may occur with moist rales, frothy sputum, and high pulse pressure. Treat

symptomatically.

5. FIRE-FIGHTING MEASURES

Suitable extinguishing media

Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

Unsuitable extinguishing media Caution: Use of water spray when fighting fire may be inefficient.

Specific hazards arising from the chemical

The product causes burns of eyes, skin and mucous membranes. Thermal decomposition can lead to release of irritating and toxic gases and vapors. In the event of fire and/or explosion do not breathe fumes.

Explosion data

Sensitivity to Mechanical Impact None. Sensitivity to Static Discharge None.

Protective equipment and precautions for firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

Personal precautions Evacuate personnel to safe areas. Use personal protective equipment as required. Avoid

contact with skin, eyes or clothing. Keep people away from and upwind of spill/leak.

Environmental precautions

Environmental precautions Do not allow into any sewer, on the ground or into any body of water. Should not be

released into the environment. Prevent further leakage or spillage if safe to do so. Prevent

product from entering drains.

Methods and material for containment and cleaning up

Methods for containment Prevent further leakage or spillage if safe to do so.

Methods for cleaning upDilute material with dilute acetic acid (vinegar) to a pH of less than 10.

7. HANDLING AND STORAGE

Precautions for safe handling

Advice on safe handling Use personal protective equipment as required. Avoid contact with skin, eyes or clothing.

Ensure adequate ventilation, especially in confined areas. In case of insufficient ventilation,

wear suitable respiratory equipment.

Conditions for safe storage, including any incompatibilities

Storage Conditions Keep containers tightly closed in a dry, cool and well-ventilated place. Keep out of the reach

of children. Keep in properly labeled containers.

Incompatible materials Strong acids and oxidizing agents. Strong acids. Aluminum.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Control parameters

Exposure Guidelines This product, as supplied, does not contain any hazardous materials with occupational

exposure limits established by the region specific regulatory bodies.

Chemical Name	ACGIH TLV	OSHA PEL	NIOSH IDLH
Potassium Hydroxide 1310-58-3	Ceiling: 2 mg/m ³	(vacated) Ceiling: 2 mg/m ³	Ceiling: 2 mg/m ³
2-butoxyethanol 111-76-2	TWA: 20 ppm	TWA: 50 ppm TWA: 240 mg/m³ (vacated) TWA: 25 ppm (vacated) TWA: 120 mg/m³ (vacated) S* S*	IDLH: 700 ppm TWA: 5 ppm TWA: 24 mg/m³
Tetrasodium Pyrophosphate 7722-88-5	-	(vacated) TWA: 5 mg/m ³	TWA: 5 mg/m ³

NIOSH IDLH Immediately Dangerous to Life or Health

Other Information Vacated limits revoked by the Court of Appeals decision in AFL-CIO v. OSHA, 965 F.2d 962

(11th Cir., 1992).

Appropriate engineering controls

Engineering Controls Showers, Eyewash stations & Ventilation systems.

Individual protection measures, such as personal protective equipment

Eye/face protection Tight sealing safety goggles.

Skin and body protectionWear impervious protective clothing, including boots, gloves, lab coat, apron or coveralls,

as appropriate, to prevent skin contact.

respiratory protection should be worn. Positive-pressure supplied air respirators or air purifying respirators may be required for high airborne contaminant concentrations. Respiratory protection must be provided in accordance with current local regulations.

General Hygiene When using do not eat, drink or smoke. Avoid contact with skin, eyes or clothing. Wear

suitable gloves and eye/face protection. Take off all contaminated clothing and wash it before reuse. Contaminated work clothing should not be allowed out of the workplace.

9. PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and chemical properties

Physical state Liquid

Appearance Colorless to Very Pale Yellow

Odor Surfactant

Odor threshold No Information available

<u>Property</u> <u>Values</u> <u>Remarks • Method</u>

pH 11.0-13.0 1% solution

Specific Gravity 1.105

Viscosity
No Information available
Melting point/freezing point
No Information available

Boiling point / boiling range > 212 ° F Flash point N/D

Evaporation rate < 1 (butyl acetate = 1)

Flammability (solid, gas) No Information available

Upper flammability limit:N/ALower flammability limit:N/AVapor pressureN/AVapor densityN/A

Water solubility completely soluble
Partition Coefficient No Information available

(n-octanol/water)

Autoignition temperature No Information available No Information available

Other Information

Density Lbs/Gal No Information available

VOC Content (%) 4.43

10. STABILITY AND REACTIVITY

Reactivity

No data available

Chemical stability

Stable under recommended storage conditions.

Possibility of Hazardous Reactions

None under normal processing.

Conditions to avoid

Elevated temperature.

Incompatible materials

Strong acids and oxidizing agents. Strong acids. Aluminum.

Hazardous Decomposition Products

Thermal decomposition can lead to release of irritating and toxic gases and vapors. Oxides of carbon.

11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

Product Information No data available

Inhalation Causes burns.

Eye contact Corrosive to the eyes and may cause severe damage including blindness.

Skin Contact The product causes burns of eyes, skin and mucous membranes.

Ingestion Causes burns. May be harmful if swallowed.

Chemical Name	Oral LD50	Dermal LD50	Inhalation LC50
Potassium Hydroxide 1310-58-3	= 284 mg/kg(Rat)	-	-
2-butoxyethanol 111-76-2	= 470 mg/kg(Rat)	= 99 mg/kg(Rabbit)	= 450 ppm (Rat) 4 h
Sodium Dodecylbenzene Sulfonate 25155-30-0	= 438 mg/kg (Rat) = 500 mg/kg (Rat)	-	-
Sodium Metasilicate 6834-92-0	= 600 mg/kg(Rat)	-	-
Sodium Nitrite 7632-00-0	= 85 mg/kg (Rat)	-	= 5.5 mg/L (Rat)4 h

Information on toxicological effects

Symptoms No Information available.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Corrosivity Causes burns. Extremely corrosive and destructive to tissue. Risk of serious damage to

eyes.

SensitizationNo Information available.Germ cell mutagenicityNo Information available.

Carcinogenicity The table below indicates whether each agency has listed any ingredient as a carcinogen.

Chemical Name	ACGIH	IARC	NTP	OSHA
2-butoxyethanol	A3	Group 3	-	-
111-76-2				

ACGIH (American Conference of Governmental Industrial Hygienists)

A3 - Animal Carcinogen

IARC (International Agency for Research on Cancer)

Not classifiable as a human carcinogen

Reproductive toxicity
STOT - single exposure
STOT - repeated exposure
Chronic toxicity

No Information available.
No Information available.
Chronic exposure to corro

Chronic exposure to corrosive fumes/gases may cause erosion of the teeth followed by jaw necrosis. Bronchial irritation with chronic cough and frequent attacks of pneumonia are common. Gastrointestinal disturbances may also be seen. Avoid repeated exposure. Possible risk of irreversible effects. May cause adverse effects on the bone marrow and

blood-forming system. May cause adverse liver effects.

Target organ effects Blood, Central nervous system, EYES, hematopoietic system, Kidney, Liver, Respiratory

system, Skin.

Aspiration hazard No Information available.

Numerical measures of toxicity - Product Information

The following values are calculated based on chapter 3.1 of the GHS document .

12. ECOLOGICAL INFORMATION

Ecotoxicity

10.91% of the mixture consists of components(s) of unknown hazards to the aquatic environment

Chemical Name	Algae/aquatic plants	Fish	Crustacea
Potassium Hydroxide 1310-58-3	-	80: 96 h Gambusia affinis mg/L LC50 static	-
2-butoxyethanol 111-76-2	-	1490: 96 h Lepomis macrochirus mg/L LC50 static 2950: 96 h Lepomis macrochirus mg/L LC50	1000: 48 h Daphnia magna mg/L EC50 1698 - 1940: 24 h Daphnia magna mg/L EC50
Sodium Tripolyphosphate 7758-29-4	-	1650: 48 h Leuciscus idus mg/L LC50	-
Sodium Dodecylbenzene Sulfonate 25155-30-0	-	10.8: 96 h Oncorhynchus mykiss mg/L LC50 static	-
Linear Dodecyl Benzene Sulphonic Acid 27176-87-0	29: 96 h Pseudokirchneriella subcapitata mg/L EC50	10.8: 96 h Oncorhynchus mykiss mg/L LC50 static 3.5 - 10: 96 h Brachydanio rerio mg/L LC50 static	5.88: 48 h Daphnia magna mg/L EC50
Sodium Metasilicate 6834-92-0	-	210: 96 h Brachydanio rerio mg/L LC50 semi-static 210: 96 h Brachydanio rerio mg/L LC50	216: 96 h Daphnia magna mg/L EC50
2-Ethyl Hexanol 104-76-7	11.5: 72 h Desmodesmus subspicatus mg/L EC50	32 - 37: 96 h Oncorhynchus mykiss mg/L LC50 static 7.5: 96 h Oncorhynchus mykiss mg/L LC50 27 - 29.5: 96 h Pimephales promelas mg/L LC50 flow-through 29.7: 96 h Pimephales promelas mg/L LC50 static 10.0 - 33.0: 96 h Lepomis macrochirus mg/L LC50 static	39: 48 h Daphnia magna mg/L EC50
Sodium Nitrite 7632-00-0	-	0.4 - 0.6: 96 h Oncorhynchus mykiss mg/L LC50 semi-static 0.65 - 1: 96 h Oncorhynchus mykiss mg/L LC50 static 2.3: 96 h Pimephales promelas mg/L LC50 flow-through 20: 96 h Pimephales promelas mg/L LC50 static 0.19: 96 h Oncorhynchus mykiss mg/L LC50 flow-through 0.092 - 0.13: 96 h Oncorhynchus mykiss mg/L LC50 flow-through mykiss mg/L LC50 flow-through	•
Sulfuric Acid 7664-93-9	-	500: 96 h Brachydanio rerio mg/L LC50 static	29: 24 h Daphnia magna mg/L EC50

Persistence and degradability

No Information available.

Bioaccumulation

No Information available.

Chemical Name	Partition coefficient
Potassium Hydroxide 1310-58-3	0.83
2-butoxyethanol 111-76-2	0.81

Other adverse effects

No Information available.

13. DISPOSAL CONSIDERATIONS

Waste treatment methods

Disposal of wastes Disposal should be in accordance with applicable regional, national and local laws and

regulations.

Contaminated packaging Do not reuse container.

This product contains one or more substances that are listed with the State of California as a hazardous waste.

Chemical Name	California Hazardous Waste Status
Potassium Hydroxide	Toxic
1310-58-3	Corrosive

14. TRANSPORT INFORMATION

The shipping classification information in this section (Section 14) is meant as a guide to the overall classification of the product. However, transportation classifications may be subject to change with changes in package size. Consult shipper requirements under 49 CFR, IATA and IMDG to assure regulatory compliance.

DOT

DOT Proper Shipping name UN1760, Corrosive liquid, n.o.s. (contains potassium hydroxide), 8, PG II

15 REGUI	ATORY IN	FORMATION
IJ. INEGGE	\neg \cup \cup \cup \cup \cup \cup	

International Inventories

TSCA Complies **DSL/NDSL** Complies **EINECS/ELINCS** Complies **ENCS** Does not comply **IECSC** Complies Complies **KECL** Complies **PICCS AICS** Complies

Legend:

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory.

DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List.

EINECS/ELINCS - European Inventory of Existing Chemical Substances/European List of Notified Chemical Substances.

ENCS - Japan Existing and New Chemical Substances

IECSC - China Inventory of Existing Chemical Substances

KECL - Korean Existing and Evaluated Chemical Substances

PICCS - Philippines Inventory of Chemicals and Chemical Substances

AICS - Australian Inventory of Chemical Substances

US Federal Regulations

SARA 313

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372.

SARA 311/312 Hazard Categories

Acute health hazard	Yes
Chronic Health Hazard	Yes
Fire hazard	No
Sudden release of pressure hazard	No
Reactive Hazard	No

CWA (Clean Water Act)

This product does not contain any substances regulated as pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42).

Chemical Name	CWA - Reportable Quantities	CWA - Toxic Pollutants	CWA - Priority Pollutants	CWA - Hazardous Substances
Potassium Hydroxide 1310-58-3	1000 lb	-	-	Х
Sodium Dodecylbenzene Sulfonate 25155-30-0	1000 lb	-	-	Х

CERCLA

This material, as supplied, does not contain any substances regulated as hazardous substances under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302) or the Superfund Amendments and Reauthorization Act (SARA) (40 CFR 355). There may be specific reporting requirements at the local, regional, or state level pertaining to releases of this material.

Chemical Name	Hazardous Substances RQs	CERCLA/SARA RQ	Reportable Quantity (RQ)
Potassium Hydroxide	1000 lb	-	RQ 1000 lb final RQ
1310-58-3			RQ 454 kg final RQ
Sodium Dodecylbenzene Sulfonate	1000 lb	-	RQ 1000 lb final RQ
25155-30-0			RQ 454 kg final RQ

US State Regulations

California Proposition 65

This product does not contain any Proposition 65 chemicals.

U.S. State Right-to-Know Regulations

Chemical Name	New Jersey	Massachusetts	Pennsylvania
Potassium Hydroxide 1310-58-3	X	X	X
2-butoxyethanol 111-76-2	Х	X	X
Sodium Dodecylbenzene Sulfonate 25155-30-0	X	X	X
Tetrasodium Pyrophosphate 7722-88-5	Х	X	X
2-Ethyl Hexanol 104-76-7	-	X	X
Sodium Trimetaphosphate 7785-84-4	-	X	X
Sodium Nitrite 7632-00-0	Х	X	X
Sodium Sulfate 7757-82-6	-	X	X

U.S. EPA Label Information

EPA Pesticide Registration Number Not Applicable

40	OTLIED	INITO		TION
16	OTHER	INE()	κ_{M}	

Health hazards 3 Flammability 1 Physical hazards N/A Personal protection X

Legend

N/E - Not Established N/D - Not Determined N/K - Not Known

Issue Date01-Apr-2013Revision Date19-May-2015Revision NoteNew format

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

End of Safety Data Sheet